



VENUS PRO SMALL BORE

GREAT IN SMALL THINGS

If it is true that small things make great changes, get ready to experience precision shooting otherwise with our new Victrix Venus PRO Small Bore.

Small caliber, great performance.

 **VICTRIX**
A R M A M E N T S

VENUS PRO SB

DATA SHEET

Destination use

Sporting ideal for dynamic long range precision shooting

Caliber / Twist rate

.22 L.R. (1/16)

Barrel length

22"
24"
26"

Weight

6,24 kg (13.76 lb) with an empty magazine, with muzzle thread protector, barrel length 22" and no scope

6,44 kg (14.20 lb) with an empty magazine, with muzzle thread protector, barrel length 24" and no scope

6,64 kg (14.64 lb) with an empty magazine, with muzzle thread protector, barrel length 26" and no scope

Dimension

Closed overall length: 804 mm (31.65")

Open overall length: 1043 mm (41.06")

With muzzle thread protector and barrel length 22"

Closed overall length: 855 mm (33.66")

Open overall length: 1094 mm (43.07") With muzzle thread protector and barrel length 24"

Closed overall length: 906 mm (35.66")

Open overall length: 1145 mm (45.08")

With muzzle thread protector and barrel length 26"

Base rifle

Hammer-forged rifled barrel in special steel with bull barrel contour

Barrel muzzle thread M18x1mm

Buttstock with horizontal and vertical multiple button adjustments and an adjustable insulated cheek piece, equipped with an Picatinny rail on the underside

Single feed and single stack 10-round magazine

Reversible EVO button folding system

High-strength monobloc chassis in light alloy ready to mount accessories or hold ammunition, and an ergonomic thumb rest

Light profile forend in light alloy equipped with a side M-LOK® system, an integrated Anschutz-type rail in the middle and an integrated Arca rail that run the entire length

Interchangeable barricade stop to protect the magazine

Wider trigger guard

Ergonomic and interchangeable zero angle grip for standard AR platform

Muzzle thread protector

Action in AISI 630 worked out from billet with a 20 MoA rail in light alloy

Bolt with two asymmetric rear lugs arranged at an angle of 60-degree lift, with a quick disassembly system and a double extractor

PVD finish on the action and on the bolt

Victrix Sporting Plus Single-stage adjustable trigger with a two-position safety: standard setting approx. 250 gr (8.82 oz)

Explorer Cases case for transport cod. 13513

Explorer Cases case for transport cod. 13513

Explorer Cases case for transport cod. 13513

User manual and welcome kit

Stock colour

Every and each component made of light alloy undergoes a 30 micron hard black anodising

CERAKOTE ceramic polymer firearm coatings available in colour: Hit Blue

Optional

45 MoA action rail in light alloy

Handguard cover on the front with a 20 MoA Picatinny rail 172,5 mm (6.79")

Handguard cover on the front with a 20 MoA Picatinny rail 296 mm (11.65")

Side forend weights for M-LOK® system

Hit Blue 



VICTRIX
SMALL BORE