



PUGIO V

SHORT IS BETTER.

Victrix Pugio is the most compact system in our catalogue, designed for urban sniping. Lighter, easier to carry, and designed following the specific needs of special forces: small dimensions and concealed transport. No one says you need a bigger rifle to hit your target.

 **VICTRIX**
A R M A M E N T S

Destination use

Law Enforcement
Military
Sporting

Caliber

.308 Win. (1/10)

Barrel length

16"

Weight

5.7 kg (12.57 lb) with an empty magazine, muzzle brake, barrel length 16" and no scope

Dimension

Closed overall length: 714 mm (28.11")

Open overall length: 960 mm (37.80")

With muzzle brake and barrel length 16"

Base rifle

Benchmark lapped match-grade button rifled barrel in AISI 416R
Buttstock with horizontal and vertical multiple lever adjustments,
a retractable monopod with quick positioning adjustment and fine
adjustment, and an insulated cheek piece

Single feed and single stack 7-round magazine

Reversible EVO button folding system

Octagonal elliptic forend with M-LOK® system, a 20 MoA integrated monobloc top rail and an integrated monobloc rail for mounting a bipod according to STANAG 4694/Mil std 1913

Ergonomic and interchangeable zero angle flat top grip for standard AR platform

20 MoA action rail according to STANAG 4694/Mil std 1913

Detachable multifunction carry handle with quick mount:

- with QM (Quick mount) attachment for picatinny rail
- ergonomic handle
- integrated picatinny rail
- hook for rope attachment
- QD (Quick detach) attachments
- tripod attachment with 1/4" – 20 UNC and 3/8" – 16 UNC threads
- front magnetic bit holder for field maintenance

Victrix ProAngle detachable muzzle brake featuring 3 forward-canted chambers

Short action in AISI 630 worked out from billet through milling and turning with finish on electro-discharge and grinding machinery.

Bolt with three asymmetric lugs: first lug on top of the cylinder in vertical position (at 12 o'clock), two side lugs arranged at an angle of 105 degree lift, dirt/ice grooves integral

PVD finish on the action and on the bolt

Victrix Professional Dual-stage trigger, convertible to a single stage trigger, with two positions top safety: standard setting approx.

1000 gr (35.27 oz)

Explorer Cases case for transport cod. 7814

User manual and welcome kit

Stock colour

Every and each component made of light alloy undergoes a hard black anodising

CERAKOTE ceramic polymer firearm coatings available in three colours:

Dark Grey

Dark Olive Drab Green

Medium Flat Brown

Optional

Side picatinny rails for forend with M-LOK® system according to STANAG 4694/Mil std 1913

