



SCORPIO V

OF A CERTAIN CALIBER .
THE MOST WELL-KNOWN.

Victrix Scorpio is born to be the ideal firearm for military sniping, with its .338 Lapua Magnum caliber. We've decided to join the most renowned ammunition with an equally reliable rifle

 **VICTRIX**
A R M A M E N T S

SCORPIO V

DATA SHEET

Destination use

Law Enforcement
Military
Sporting

Caliber

.338 Lapua Magnum (1/10)
.300 Win. Magnum (1/10)
.300 Norma Magnum (1/10)

Barrel length

22"
26"

Weight

6.4 kg (14.11 lb) with an empty magazine, muzzle brake, barrel length 22" and no scope

6.7 kg (14.77 lb) with an empty magazine, muzzle brake, barrel length 26" and no scope

Dimension

Closed overall length: 902 mm (35.51")
Open overall length: 1148 mm (45.20")
With muzzle brake and barrel length 22"

Closed overall length: 1004 mm (39.53")
Open overall length: 1250 mm (49.21")
With muzzle brake and barrel length 26"

Base rifle

Benchmark lapped match-grade button rifled barrel in AISI 416R
Buttstock with horizontal and vertical multiple lever adjustments, a retractable monopod with quick positioning adjustment and fine adjustment, and an insulated cheek piece
Single feed and single stack 7-round magazine
Reversible EVO button folding system
Octagonal elliptic forend with M-LOK® system, a 20 MoA integrated monobloc top rail and an integrated monobloc rail for mounting a bipod according to STANAG 4694/Mil std 1913
Ergonomic and interchangeable zero angle flat top grip for standard AR platform
20 MoA action rail according to STANAG 4694/Mil std 1913
Detachable multifunction carry handle with quick mount:

- with QM (Quick mount) attachment for picatinny rail
- ergonomic handle
- integrated picatinny rail
- hook for rope attachment
- QD (Quick detach) attachments
- tripod attachment with 1/4" – 20 UNC and 3/8" – 16 UNC threads
- front magnetic bit holder for field maintenance

Victrix ProAngle detachable muzzle brake featuring 3 forward-canted chambers
Long action in AISI 630 worked out from billet through milling and turning with finish on electro-discharge and grinding machinery.
Bolt with three asymmetric lugs: first lug on top of the cylinder in vertical position (at 12 o'clock), two side lugs arranged at an angle


of 105 degree lift, dirt/ice grooves integral
Matt PVD finish on the action and polished PVD finish on the bolt
Victrix Professional Dual-stage trigger, convertible to a single stage trigger, with two positions top safety: standard setting approx. 1000 gr (35.27 oz)
Explorer Cases for transport cod. 13513
User manual and welcome kit

Stock colour

Every and each component made of light alloy undergoes a hard black anodising
CERAKOTE ceramic polymer firearm coatings available in three colours:
Dark Grey
Dark Olive Drab Green
Medium Flat Brown

Optional

Side picatinny rails for forend with M-LOK® system according to STANAG 4694/Mil std 1913



VICTRIX
PROFESSIONAL