



VENUS V

THE TOOL OF THE TRADE.

Do you really play your sport with the first things you have around?

Leave assemblies and adjustments to the other.

Let us present you our Victrix Venus, the first European rifle designed for Precision Rifle Series® shooting, ready for delivery and in different versions.

Leave the unexpected to your competitors.

 **VICTRIX**
A R M A M E N T S

Destination use

Sporting ideal for PRS® shooting

Caliber / Twist rate

6 XC (1/7.5)
6,5 x 47 Lapua (1/8)
6,5 x 47 Lapua (1/8.5)
6,5 Creedmoor (1/8)
6,5 Creedmoor (1/8.5)
6 Creedmoor (1/7.5)
.260 Remington (1/8.5)
.308 Winchester (1/11)

Barrel length

24"

Weight

5,55 kg (12.24 lb), with an empty magazine, muzzle brake, barrel length 24" and no scope

Dimension


Overall length: 1170 mm (46.06")
With muzzle brake and barrel length 24"

Base rifle

Benchmark lapped match-grade button rifled barrel in AISI 416R, CERAKOTE black matt finish
Buttstock with horizontal and vertical multiple button adjustments and an adjustable insulated cheek piece, equipped with an Anschutz-type rail on the underside
Single-feed and single stack 7-round polymer magazine
High-strength monobloc chassis in light alloy
Light profile forend in light alloy equipped with a side M-LOK® system and QD (Quick Detach) attachments, an integrated Anschutz-type rail in the middle and an integrated Arca rail that runs the entire length
Ergonomic and interchangeable zero angle flat top grip for standard AR platform
20 MoA action rail
Victrix ProAngle Venus V detachable muzzle brake featuring 4 forward-canted chambers
Short action in AISI 630 worked out from billet through milling and turning with finish on electro-discharge and grinding machines.
Bolt with three asymmetric lugs: first lug on top of the cylinder in vertical position (at 12 o'clock) and two side lugs arranged at an angle of 105-degree lift; equipped with grooves and an interchangeable bolt lever
PVD finish on the action and on the bolt
Victrix Sporting Plus Single-stage adjustable trigger with a two-position safety: standard setting approx. 400 gr (14.11 oz)
Explorer Cases case for transport cod. 13513
User manual and welcome kit

Stock colour

Every and each component made of light alloy undergoes a hard black anodising.
Victrix Venus V is available in the following finishes:
Orobic-blue, CERAKOTE ceramic polymer coating
Hard black anodised

Hard Black Anodised 
Orobic-Blue 