

V-MAX 40 gr



Bullet type	Bullet weight	Ballistic coefficient	Product number
Hornady V-Max	2.6 g / 40 gr	0.2	20157052

Velocity			
V ₀	V ₁₀₀	V ₂₀₀	V ₃₀₀
1050 (m/s) / 3445 (f/s)	881 (m/s) / 2936 (f/s)	732 (m/s) / 2482 (f/s)	598 (m/s) / 2070 (f/s)

Energy			
E ₀	E ₁₀₀	E ₂₀₀	E ₃₀₀
1434 (J) / 1054 (ft.-lb.)	1010 (J) / 766 (ft.-lb.)	697 (J) / 577 (ft.-lb.)	465 (J) / 381 (ft.-lb.)

Zero range, meters	Height of trajectory above line of sight if sighted in at X meter. For sights 40mm above bore					
	50	80	100	150	200	300 m
80	-7	å	-1	-26	-90	-365
100	-7	1	å	-25	-88	-362
150	2	14	17	å	-55	-312
200	15	36	44	41	å	-230

Sighting distance in yards	Height of trajectory above line of sight if sighted in at X yards. For sights 1,6 inch above bore				
	50	100	150	200	300 yds
50	å	0.7	0.5	-1	-8.4

100	-0.4	å	-0.6	-2.5	-10.7
150	-0.2	0.4	å	-1.6	-9.4
200	0.3	1.2	1.2	å	-7

Winddrift in mm for a 5 m/s cross wind

100	200	300 m
44	190	470

Winddrift in inches for a 10 m.p.h cross wind

100	200	300 yds
1.3	5.5	13.5

NORMA PRECISION AB
670 40 Åmotfors
Sweden



Sweden, since 1988.

Purveyor
to the
Royal
Court
of



Together
ahead. **RUAG**