

# Norma Kalahari 125 gr



| Bullet type    | Bullet weight  | Ballistic coefficient | Product number |
|----------------|----------------|-----------------------|----------------|
| Norma Kalahari | 8.1 g / 125 gr | 0.315                 | 20170892       |

| Velocity               |                        |                        |                        |
|------------------------|------------------------|------------------------|------------------------|
| V <sub>0</sub>         | V <sub>100</sub>       | V <sub>200</sub>       | V <sub>300</sub>       |
| 945 (m/s) / 3100 (f/s) | 844 (m/s) / 2795 (f/s) | 749 (m/s) / 2510 (f/s) | 661 (m/s) / 2242 (f/s) |

| Energy                    |                           |                           |                           |
|---------------------------|---------------------------|---------------------------|---------------------------|
| E <sub>0</sub>            | E <sub>100</sub>          | E <sub>200</sub>          | E <sub>300</sub>          |
| 3618 (J) / 2688 (ft.-lb.) | 2884 (J) / 2169 (ft.-lb.) | 2276 (J) / 1749 (ft.-lb.) | 1773 (J) / 1396 (ft.-lb.) |

| Zero range, meters | Height of trajectory above line of sight if sighted in at X meter. For sights 40mm above bore |    |     |     |      |       |
|--------------------|-----------------------------------------------------------------------------------------------|----|-----|-----|------|-------|
|                    | 50                                                                                            | 80 | 100 | 150 | 200  | 300 m |
| 80                 | -6                                                                                            | å  | -3  | -34 | -104 | -381  |
| 100                | -5                                                                                            | 2  | å   | -30 | -99  | -373  |
| 150                | 5                                                                                             | 18 | 2   | å   | -59  | -313  |
| 200                | 20                                                                                            | 42 | 50  | 44  | å    | -225  |

| Sighting distance in yards | Height of trajectory above line of sight if sighted in at X yards. For sights 1,6 inch above bore |     |      |      |         |
|----------------------------|---------------------------------------------------------------------------------------------------|-----|------|------|---------|
|                            | 50                                                                                                | 100 | 150  | 200  | 300 yds |
| 50                         | å                                                                                                 | 0.6 | 0.1  | -1.7 | -9.5    |
| 100                        | -0.3                                                                                              | å   | -0.8 | -2.9 | -11.3   |

|            |     |     |     |      |      |
|------------|-----|-----|-----|------|------|
| <b>150</b> | 0   | 0.5 | å   | -1.8 | -9.7 |
| <b>200</b> | 0.4 | 1.4 | 1.3 | å    | -7   |

| Winddrift in mm for a 5 m/s cross wind |            |              |
|----------------------------------------|------------|--------------|
| <b>100</b>                             | <b>200</b> | <b>300 m</b> |
| 31                                     | 130        | 310          |

| Winddrift in inches for a 10 m.p.h cross wind |            |                |
|-----------------------------------------------|------------|----------------|
| <b>100</b>                                    | <b>200</b> | <b>300 yds</b> |
| 0.9                                           | 3.8        | 9              |

**NORMA PRECISION AB**  
670 40 Åmotfors  
Sweden



Sweden, since 1988.

Purveyor  
to the  
Royal  
Court  
of



Together  
ahead. **RUAG**